

Frigelux®

MINIBAR40VE

Minibar

Free standing installation



- + **Gross volume: 40 L**
Global net volume: 34 L
- + New Energy Class: E
- + Design: black
- + Adjustable temperature range of use:
5-17°C
- + LED lights
- + Automatic defrost
- + 1 reversible glass door glass, integrated handle



Eco-responsibility

Our products are manufactured in compliance with European environmental rules. Especially, refrigerant fluid (R600a) doesn't reject neither CFC nor HFC and respect environment.

Frigelux[®]

MINIBAR40VE Minibar Free standing installation



> EQUIPMENTS INCLUDED

- 2 wire shelves

> TECHNICAL CHARACTERISTICS

- Annual electrical consumption: 75 kWh
- Climate class: N (16°C - 32°C)
- Noise level: 22 dB
- Voltage: 220-240 V
- Power input: 58 W
- Category: 10 - Multi-use and other refrigerating
- Type of gas: R600a

> LOGISTIC DATAS

Gross dimensions (WxDxH cm)	:	46 x 50 x 59
Net dimensions (WxDxH cm)	:	40,2 x 43 x 54,8
Gross weight (kg)	:	14.00
Net weight (kg)	:	13.00
Full truck (pcs)	:	0
Container (pcs)	20'	: 0
	40'	: 0
	40' HC	: 0

Gencod	3541362405043
--------	---------------